

PN UNI by Roto

Projecting Side Hung Gearing

CYCLE TESTED
20,000
CYCLES

MECHANICAL
GUARANTEE
10
YEARS

Carl F
Groupco




- Recommended maximum sash width 806mm (height should always exceed width)
- Glazed sash weight max 50kg
- Built in adjustable friction for flexible control of opening
- Emergency egress escape opening can be achieved (providing building regulations are met)

The built in adjustable friction gives high durability and stability to the window. This variant is supplied with a bottom rail suitable for timber, plastic and aluminium profiles.

The projecting side hung is capable of achieving emergency escape (providing that all relevant building regulations are met).

The sash and frame detail are the same for all window PN UNI variants, allowing styles to be fitted without changing profile routing. This ensures a uniform aesthetic appearance on all window styles.



Technical Information:

- Recommended maximum sash width: 806mm (height should always exceed width)
- Glazed sash weight max: 50kg

Description	Part Code		Box Qty
	Left Hand	Right Hand	
Projecting Side Hung for Timber			
To Fit Sash 250mm – 806mm	3728-2	3728-1	5
Projecting Side Hung for PVCu and Aluminium			
To Fit Sash 250mm – 806mm	3729-2	3729-1	5

NB: Items are handed viewed externally.