

# Securistyle Defender Plus

## Heavy Duty Friction Stay

MECHANICAL  
GUARANTEE  
**10  
YEARS**

MECHANICAL  
GUARANTEE  
**12  
YEARS**

Carl F  
Groupco

**securistyle** <sup>®</sup>

CYCLE  
TESTED  
**30,000  
CYCLES**

- Up to 50kg top hung, and 40kg side hung loads
- Enhanced weather sealing
- Smooth operation

The Defender Plus, heavy duty friction stay is able to carry loads of up to 50kg for top hung windows and 40kg for side hung windows.

An asymmetric location system allows for reliable and accurate closure, while weather sealing and draft proofing is improved by an asymmetrical vent arm.

The top hung variant features slot - hole - slot vent fixing configuration for ease of adjustment and guaranteed fixing into reinforcement on PVCu window frames.

The enclosed end cap prevents ingress of debris and provides increased cavity tolerance.



### Material Specification:

The Defender Plus is available with a 10 or 12 year guarantee, depending upon the material selection:

- Standard ferretic steel to BS EN 10088-2 Grade 1, 4016 offers a 10 year guarantee
- Austenitic stainless steel to BS EN 10088-2 Grade 1, 4301 for enhanced corrosion resistance offers a 12 year guarantee (available to order only)

### Technical Information:

#### Sizes:

- Available in 24" top hung
- Available in 13mm or 17mm stack heights

Side Hung	Highline		Max Vent Weight (kg)	Min Vent Width (mm)	Max Vent Width (mm)	Opening Angle (+/- 2.5°)
13-14mm	16-17mm	17-18mm				
Securistyle Defender Plus Heavy Duty Friction Stay						
EDTH24	EDTH24H6	EDTH24H7	50	850	1500	32°

Austenitic steel version available.